

TT24-7NRT™

Specification sheet

The TT24-7NRT is a near-real-time, tandem trap thermal desorption (TD) system for continuous sampling and concentration of volatile and semi-volatile organic vapours in air or gas.

1. System features

- **Tandem-trap continuous monitoring** – Two sorbent packed traps operate in tandem to ensure 100% sample coverage.
- **Standalone automatic sampling and pre-concentration** that can be connected to any make of GC, fast GC, and various real-time vapour detectors.
- **Compatible with gas-phase samples** ranging in pressure from below atmospheric to 50 psig.
- **Wide range of sampling flows** – up to 800 mL/min from atmospheric pressure samples offers high sensitivity with fast cycle time.
- **Electrical cooling** – delivers robust, reproducible cycle times and quantitative analyte retention without any liquid cryogen.
- **Optimised for fast cycle times** – as low as 5 minutes for single agent monitoring.
- **Multi-Gas enabled** – compatibility with helium, hydrogen and nitrogen carrier gas provides the flexibility to meet operational and analytical priorities.
- **Easy-change consumables, sub-ambient trapping, and efficient backflush desorption** deliver maximum flexibility with the same system supporting screening of wide-ranging target and untargeted lists, including analysis of highly volatile toxic industrial chemicals and less volatile chemical agents with a simple consumable change.
- **Inert, uniformly heated flow path** compatible with highly reactive nerve and blister agents at worker protection levels (WPLs) and general population limit levels (GPLs).



- **Ultra-rapid trap desorption** optimises separation and sensitivity delivering narrow peaks even under spitless analytical conditions.
- **Internal standard addition (optional)** – enables a precise aliquot (via a 1 mL loop) of gas phase standard to be added onto either focusing trap for accuracy, quality control, and instrument confidence.
- **Leak test:** automatic checks of the instrument without user intervention including both traps, tube, and split flows to ensure sample integrity, and provide data confidence.
- **Tube desorption mode** facilitates single sorbent tube analysis for confirmation and troubleshooting.
- **Re-collection of split flows** onto sorbent packed tubes enables simple method validation, troubleshooting and confirmatory analysis with a different detector.
- **Intelligent PC-based software optimised for remote deployment:** continuous system health monitoring and automated self-diagnostic routines support unattended operation. Preventative maintenance feedback indicates when parts could be replaced to avoid instrument downtime.

2. Physical

Dimensions	H 45 cm (17.7") × W 32 cm (12.6") × D 52 cm (20.5").
Weight	26 Kg (57 lb).

3. Gas selection

Carrier gas	0–60 psig of hydrogen, helium, or nitrogen at 2–500 mL/min.
Sample gas	Air, helium, and nitrogen.
Pneumatics gas	Dry (dew point -50°C or below) air or nitrogen in the range 50–60 psig.

4. Gas generator requirements*

Carrier gas	Minimum capacity 200 mL/min but will be method dependant. Purity 5.5 or better.
Pneumatics gas	150 mL/min continuous consumption. Minimum capacity of 1 L/min at 100 psi with integrated compressor and 2.5 m of 1/4" tubing to provide buffer volume to accommodate short term peak gas demand. Dew point <-50°C Purity 5.0 or better.

5. Sampling Flows

Atmospheric pressure source	20–800 mL/min .
Pressurised source	20–1000 mL/min.**

6. Operating Temperatures

Flow path	50°C–210°C.
Trap low	-30°C–50°C.***
Trap high	35°C–425°C.

7. Environmental operating conditions

Temperature	15°C–30°C.
Relative humidity	5–95% RH (non-condensing).
Altitude	Up to 2000 m (~6500 ft).

8. Operating requirements

Power	100–240 V, 50/60 Hz, 1200 W (TT24-7NRT self-adjusts to local voltage input).
-------	--

9. Minimum PC Specification

For TD control:

- CPU: 1 GHz 64-bit dual-core or better.
- RAM: 4 GB.
- Hard disk space: 2 GB.
- Graphics card: DirectX 9 or later.
- Display: 1024 × 768 display.
- Operating system: Windows® 10, or 11 64-bit, English.
- Other requirements: Windows-compatible keyboard and mouse, one free USB.

*Capacity stated is for a single TT24-7NRT and may need to be increased to accommodate supply for GC detectors such as FID, FPD, or additional TT24-7NRT instruments.

**A minimum of 5 psig is required at the sample inlet. Any pressure drop across sampling accessories, or an extended sampling line will need to be taken into account.

*** Trap low temperatures of -30°C may not be attainable under all operational conditions. Factors affecting the minimum temperature may include flow path temperature and sampling flow rates in excess of 100 mL/min.

10. Safety and regulatory certifications

- The instrument is designed and manufactured under a quality system registered to ISO 9001.
- The instrument complies with the essential requirements of the following applicable European and North American Directives, and carries the CE/UKCA marks accordingly:
 - Low Voltage Directive 2014/35/EU.
 - EMC Directive 2014/30/EU.
 - ROHS Directive 2015/863/EU.
- The instrument conforms to the following product safety standards:
 - IEC 61010-1:2010/AMD1:2016.
 - IEC 61010-2-010/EN 61010-2-010:2014.
 - Canada: CSA C22.2 No.61010-1-12:2012.
 - USA: ANSI/UL 61010-1:2012.
- The instrument conforms to the following regulation on electromagnetic compatibility (EMC):
 - IEC/EN 61326-1:2021.

11. System options

U-TT24-7NRT: Twin-trap near-real-time thermal desorber with electronic flow control.

U-TT24-7NRT-IS: As above and includes factory fitted internal standard addition for introduction of gas-phase standard onto either focusing trap, providing improved precision of quantitative analysis.

12. Accessory and upgrade options

Sample pump

(U-ASPM1-H/U-ASPM2-H/U-ASPM3-H) to pull atmospheric pressure sample gas through the traps via the sample inlet.

Heated sample line (U-HSLTT) extends the sample inlet by 2 m to allow remote sampling. Sample line is heated to match flow path of 50°C-210°C.

In-line dryer (U-ASDRY-TTNRT-1): Nafion™ dryer for monitoring ultra-volatile, non-polar compounds in humid atmospheres.

DAAMS tube conversion: Kit to convert TT24-7NRT for use with 4½" tubes (U-35T045KT).

For more information about our products and services, please visit www.markes.com.

Trademarks

TT24-7NRT™ is a trademark of Markes International. Nafion™ is a trademark of DuPont.

Windows® is a registered trademark of Microsoft Corp.

Markes International shall not be liable for errors contained in this specification or for incidental or consequential damages in connection with the supply, performance or use of this equipment.

Markes International reserves the right to change information, descriptions and specifications within this document without notice.